ITEM	SERVICE	MAWP	CODE	NOZZLES		COUPLING	REF. DIMENSION		LOUVERS	BUG SCREEN	DRIVE	FAN	FINISH
				INLET	OUTLET	V&D/TEMP	B	C					
1	AC	1650 PSI @ 300/-49°F	ASME	6"-900# RFWN	6"-900# RFWN	11" 900 RFWN	–	–	NONE	YES	ELECTRIC MOTOR DRIVE SHEAVES, BELTS, AND GUARDS BY AIR-X-HEMPHILL 15 HP, 1800 RPM, 3P, 60 HZ, 460 V, XP, PE VFD, CSA, ELECTRIC MOTOR (A) VIBRATION SWITCH	132"ø MOORE 10K, 36 VT 8-BLADE 20° PA, RH ROTATION 248 RPM @ 13.9 HP REQ'D ø2.6875 BORE WITH .625 x .3125 KWY.	STRUCTURE STD. PRIMER W/ WARM GRAY ENAMEL TOP COAT FAN GUARD GALVANIZED
2	HEATING (26 GALS)	14 PSI @ 300/-20°F	NONE	2"-3000 CPLG	2"-3000 CPLG	NONE	–	–					







SECTION A-A

NOTE: ALL DIMENSIONS IN [ ] ARE MM

RELEASED
FABRICATION OF THIS ORDER HAS BEGUN

REV	REVISION DESCRIPTION	BY	CK	APP	DATE
4	ADDED MOTOR BEAM, PILINGS, GRAVEL & RELEASED	MIKE	L.W.		09/08/04
3	DELETED INT LOUVERS, CHG'D RECIR ACCESS	MIKE	L.W.		08/11/04
2	ADDED RECIR & HEATING COIL	MIKE	L.W.		08/11/04
1	PER CUSTOMER COMMENTS	MIKE	L.W.		08/02/04

FOR: BP CANADA ENERGY COMPANY
P.O. NO: D5758
CUST. TAG NUM: –
USER: BP CANADA ENERGY COMPANY
JOBSITE: B.C. CANADA
JOB NO: 48035
WORK ORDER NO: 9969
DR: S.Y. DATE: 7/8/04
CK: M.B. DATE: 7/9/04

ESTIMATED DRY WEIGHT 31,300#

air-x-hemphill
TULSA, OKLAHOMA

CERTIFIED DRAWING FOR:
MODEL 132 ZF QUANTITY: 1

– DWG. NO. 48035-CRT

SCALE: FULL DATE: 7/8/04 REV 4