



MEG ENERGY

CHRISTINA LAKE REGIONAL PROJECT  
Phase 3A EPC for Central Plant Facilities

SLI Project No. 511036



SNC-LAVALIN



SNC-LAVALIN

Vendor's drawing review for conformity with specifications and design drawing.

This review does not relieve the vendor of his responsibility for errors in design and detailing as detailed in his contract.

- A1 Not suitable to initiate fabrication. modify as noted, resubmit for review
- B1 Suitable to initiate fabrication as noted. modify as noted, resubmit for review
- C1 Suitable to fabricate to completion as noted. submit final documents including as-builts as required
- D1 Suitable to fabricate to completion. submit final documents including as-built documents as required
- E1 Not suitable as final documents as noted. modify as noted and resubmit.
- F1 Suitable as final documents. no further resubmittal required (unless revised by vendor)

Vendor: Heat Exchanger Design, Inc. - 12427

No.: TSS4565B

Rev: 1

Date Rec'd

Doc. Title: D00.01 - Thermal Data Sheet - Tag: 3A-E-397

2013/10/30

Client Code:

Project: MEG Phase 3A EPC

Reviewed by:

*[Handwritten signature]*

Document No

Submittal

Date:

*Nov. 13, 2013*

P-5330-01-0013

03

# Heat Exchanger Design, Inc.



P.O.Box 524  
Indianapolis, IN., 46205

Tel:(317)686-9000  
Fax:(317)686-9100

HEAT EXCHANGER SPECIFICATION SHEET						Page 1
Customer	MEG Energy		Job No.	4565B-1, 2, & 3		
Address			Reference No.	PO# P-5330-01		
Plant Location	Christina Lake, AB		Proposal No.	111-13		
Service of Unit	HP BFW Minimum Flow Recycle Cooler		Date	4/10/2013	Rev 2a	
Size	400 x 25.4 x 1219.2mm	Type	SH 16D92-04-00-TV-6B8B	Horz.	Conn. in	1 Parallel 1 Series
Surf/Unit (Gross/Eff)	24.63 / 24.09 m <sup>2</sup>	Shell/Unit	1	Surf/Shell (Gross/Eff)	24.63 / 24.09 m <sup>2</sup>	
PERFORMANCE OF ONE UNIT						
Fluid Allocation	Shell Side			Tube Side		
Fluid Name	TEG / H2O (60/40 wt%)			BFW		
Fluid Quantity, Total	kg/hr	49402.2			258583	
Vapor (In/Out)						
Liquid		49402.2	49402.2	258583	258583	
Steam						
Water						
Noncondensables						
Temperature (In/Out)	C	40.00	105.00	199.30	190.00	
Specific Gravity		1.0789	1.0268	0.8663	0.8769	
Viscosity	mN-s/m <sup>2</sup>	4.6610	1.3460	0.1340	0.1410	
Molecular Weight, Vapor						
Molecular Weight, Noncondensables						
Specific Heat	kJ/kg-C	3.2230	3.4560	4.4900	4.4460	
Thermal Conductivity	W/m-C	0.3280	0.3400	0.6650	0.6710	
Latent Heat	kJ/kg					
Inlet Pressure	kPa	994.002			2294.00	
Velocity	m/s	0.41			2.55	
Pressure Drop, Allow/Calc	kPa	100.000	4.507	100.000	13.668	
Fouling Resistance (min)	m <sup>2</sup> -K/W	NOTE 5			NOTE 5	
Heat Exchanged	MegaWatts	2.9789	MTD (Corrected)	119.4 C		
Transfer Rate, Service	1035.79 W/m <sup>2</sup> -K	Clean	1706.81 W/m <sup>2</sup> -K	Actual	1706.81 W/m <sup>2</sup> -K	
CONSTRUCTION OF ONE SHELL				Sketch (Bundle/Nozzle Orientation)		
Design/Test Pressure	kPaG	3339/FV / Code	4340/FV / Code			
Design Temperature	C	-28.9 / 210	-28.9 / 210			
No Passes per Shell		1	1			
Corrosion Allowance	mm	3.2	3.2 (Except tubes)			
Connections	In	inch	6" 300# RFWN	8" 300# RFWN		
Size & Rating	Out	inch	6" 300# RFWN	8" 300# RFWN		
	Intermediate					
Tube No.	92	OD 25.400 mm	Thk(Avg) 2.108 mm	Length 1.2192 m	Pitch 31.750 mm	Layout 60
Tube Type	Plain			Material	SA-179 (smls)	
Shell	SA-106B	406.4mm OD		Shell Cover	SA-516-70N	
Channel or Bonnet	SA-516-70N			Channel Cover	N/A	
Tubesheet-Stationary	SA-516-70N			Tubesheet-Floating	N/A	
Floating Head Cover	N/A			Impingement Plate	None	
Baffles-Cross	A-36	Type SINGLE-SEG. (Vert.)	%Cut (Diam) 33.00	Spacing(c/c)	304.801	
Baffles-Long	N/A		Seal Type			
Supports-Tube	A-36	U-Bend	Type			
Bypass Seal Arrangement			Tube-Tubesheet Joint	Strength Welded		
Expansion Joint	N/R		Type			
Rho-V2-Inlet Nozzle	617.43 kg/m-s <sup>2</sup>	Bundle Entrance	0.00	Bundle Exit	0.00	kg/m-s <sup>2</sup>
Gaskets-Shell Side	Kammpro Type	Tube Side	Kammpro Type			
-Floating Head	N/A					
Code Requirements	ASME Section VIII, Div. I			TEMA Class		
Weight/Shell	1626.07	Filled with Water 2089.82		Bundle	425.59	kg
Remarks: 1. This is HED's standard separated head Hairpin Exchanger with independent bolting. 2. Three (3) identical exchangers are required. 3. 50mm thick mineral wool insulation is included per specification. 4. 15% overdesign has been considered to account for potential fouling. 5. U-bends are stress relieved.						
Reprinted with Permission (v6 SP3)						